Automatic Pallet Strapping Machine

Specification of SPR-YSD

- The Pallet Strapping machine is used for strapping pallets, cartons, and wooden boxes. Mainly suitable for outer packaging of food, papermaking, dyes, plastic, glass ceramics, chemicals, mechanical and electrical products, etc.
- Packing tape reels, strapping products, and welding strapping can be completed with one machine, reducing staff and improving work efficiency.



Specification

Advantages



Adjustable tightnes

The tightness can be adjusted according to the thickness of the packing box and the products being packed to prevent the products or cartons from being damaged during the bundling process.

Belt threading structure

The improved belt threading structure simplifies the belt threading process in one step.





Shift selection switch Welding, tightening and strapping, and cutting are all done in one step.

Simple operation panel

Humanized design makes packaging more efficient and the machine parameters are easy to set



Model	SPR-YSD
Power	220V,50Hz,0.43KW
Tensioning force	0-100kg (Adjustable)
Packing width	No limit for range of width , could feed strap always.
Packing Height	Min 600 mm , no limit for Max height , 2000 mm (recommend)
Height of sealing position	542 mm
Packing Speed	≤2.2 second /per strap
Size of strap	Width9-15(±1)mm,Thickness0.6 -1.0(±0.1)mm, PP or PET Straps
Inner diameter of strap plate	200-280 mm
Length of feeding sword	1000 mm
Machine size	L900mmXW550mmXH1550mm
Machine weight	200 KGS